

# Trimod<sup>®</sup> Besta

## Trimod Besta Füllstandscharter

## Trimod Besta Level Switch

## Trimod Besta Contrôleur de niveau

|  |  |  |  |   |  |
|--|--|--|--|---|--|
|  |  |  |  | Safety Integrity Level: <b>SIL 1</b><br>(SIL 3 capable) |  |
|  |  |  |  | Dimensionen / Dimensions mm                             |  |
| A  |  | LG   |  | NG  |  |
| L  |  | X  |  | 92  |  |
| 4 x Ø 13   |  |  |  |   |  |
| Ship register certificate:<br>ABS, BV, DNV·GL, LR, RINA, RS, ClassNK   |  |  |  |   |  |
| Überwurfflansch<br>Slip-on flange --<br>Bride folle  |  |  |  |   |  |
| Schmelze / Heat no:  |  |  |  |   |  |
| Bachofen-Nr. / Bachofen no:  |  |  |  |   |  |
| Dichteinheit / Fixflansch<br>Sealing unit / Fixed flange 1.4408<br>Unité d'étanchéité / Bride fixe   |  |  |  |   |  |
| Schmelze / Heat no:  |  |  |  |   |  |
| Bachofen-Nr. / Bachofen no:  |  |  |  |   |  |
| Schwimmer<br>Float 1.4571<br>Flotteur  |  |  |  |   |  |
| Order no.  |  |  |  |   |  |
| Stk./ pcs./quant.  |  |  |  |   |  |
| Date/Visa 02.10.15 / SIA   |  |  |  |   |  |
| Gasket Ø77/64x2 Blue Gard 3000<br>Required light density: ..... kg/dm <sup>3</sup><br>Required heavy density: ..... kg/dm <sup>3</sup>   |  |  |  |   |  |
| Typ<br>Type <b>A 01 08T1</b><br>Type (Art. no. ....)   | Schaltmodul<br>Switch module <b>A</b><br>Module de commande                              | Flanschmodul<br>Flange module <b>01</b><br>Module de bride                           | Schwimmermodul<br>Float module <b>08T1</b><br>Module de flotteur   |   |  |
| Betriebstemperatur<br>Operating temp. 0 to 300°C<br>Temp. de service   | Gehäusematerial<br>Housing material Aluminium<br>Sea water resistant<br>Matériau boîtier | Nenndruck / -weite<br>Nom. Pressure / -Diameter PN 25<br>Pression- / Section Nominal | Schaltdifferenz<br>Operating diff. .... mm<br>Différentiel   |   |  |
| Umgebungstemp.<br>Ambient temp. 0 to 70°C<br>Temp. d'ambiance  | Kabeleinführung<br>Cable entry M20 x 1.5<br>Presse-étoupe                                | Norm<br>Standard Besta<br>Norme  | Dichte max. / min.<br>Density max. / min. ≤ ..... kg/dm <sup>3</sup><br>Densité max. / min. ≥ ..... kg/dm <sup>3</sup> |   |  |
| Schaltleistung<br>Switch rating 5A / 250VAC<br>5A / 30VDC<br>Pouvoir de coupure  | Schutzart<br>Enclosure IP65<br>Cl. de protection   | Dichtungsart<br>Flange Facing Raised face<br>Type d'étanchéité                       | Nenn- / Prüfdruck<br>Nominal / Test press. PN 25 bar<br>PP 38 bar<br>Pression nominal / d'épreuve                      |   |  |
| BACHOFEN<br>INDUSTRIAL AUTOMATION<br>Bachofen AG, Ackerstrasse 42<br>CH-8610 Uster/Switzerland<br>Phone +41 44 944 11 11<br>Fax +41 44 944 12 33<br>info@trimodbesta.com<br>www.trimodbesta.com 011015/TSI |  |  |  |   |  |